



Depth of Field Tables in Meter

for

ARRI/ZEISS Master Anamorphic Lenses

circle of confusion: 0.030 mm

Master Anamorphic 2x	MA 28/T1.9	T*XP
Master Anamorphic 2x	MA 35/T1.9	T*XP
Master Anamorphic 2x	MA 40/T1.9	T*XP
Master Anamorphic 2x	MA 50/T1.9	T*XP
Master Anamorphic 2x	MA 60/T1.9	T*XP
Master Anamorphic 2x	MA 75/T1.9	T*XP
Master Anamorphic 2x	MA 100/T1.9	T*XP
Master Anamorphic 2x	MA 135/T1.9	T*XP
Master Anamorphic 2x	MA 180/T2.8	T*XP

ARRI/ZEISS Master Anamorphic 2x MA 28/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	1.9		2		2.8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	13.71		12.78		9.04	
INF	13.71	INF	12.78	INF	9.04	INF
100	12.04	INF	11.31	INF	8.27	INF
50	10.75	INF	10.16	INF	7.64	INF
30	9.40	INF	8.95	INF	6.94	INF
20	8.13	INF	7.79	INF	6.22	INF
15	7.16	INF	6.90	INF	5.64	INF
12	6.40	96.18	6.19	197.14	5.15	INF
10	5.78	36.90	5.61	45.92	4.75	INF
8.0	5.05	19.18	4.92	21.35	4.25	69.19
7.0	4.64	14.28	4.53	15.45	3.95	30.90
6.0	4.18	10.65	4.09	11.29	3.61	17.78
5.0	3.67	7.86	3.60	8.20	3.22	11.15
4.5	3.39	6.69	3.33	6.93	3.01	8.93
4.0	3.10	5.64	3.05	5.81	2.78	7.15
3.5	2.79	4.69	2.75	4.81	2.53	5.69
3.0	2.47	3.83	2.43	3.91	2.26	4.48
2.8	2.33	3.51	2.30	3.58	2.14	4.04
2.6	2.19	3.20	2.16	3.26	2.02	3.64
2.4	2.05	2.90	2.02	2.95	1.90	3.26
2.2	1.90	2.62	1.88	2.65	1.77	2.90
2.0	1.75	2.34	1.73	2.37	1.64	2.56
1.9	1.67	2.20	1.66	2.23	1.57	2.40
1.8	1.59	2.07	1.58	2.09	1.50	2.24
1.7	1.52	1.94	1.50	1.96	1.43	2.09
1.6	1.44	1.81	1.42	1.83	1.36	1.94
1.5	1.35	1.68	1.35	1.70	1.29	1.79
1.4	1.27	1.56	1.26	1.57	1.22	1.65
1.3	1.19	1.43	1.18	1.44	1.14	1.51
1.2	1.11	1.31	1.10	1.32	1.06	1.38
1.1	1.02	1.19	1.02	1.20	0.98	1.25
1.0	0.93	1.08	0.93	1.08	0.90	1.12
1.0	0.89	1.02	0.89	1.02	0.86	1.06
0.9	0.85	0.96	0.84	0.97	0.82	1.00
0.9	0.80	0.90	0.80	0.91	0.78	0.94
0.8	0.76	0.85	0.75	0.85	0.74	0.88
0.78	0.74	0.83	0.74	0.83	0.72	0.85
0.76	0.72	0.80	0.72	0.81	0.70	0.83
0.74	0.70	0.78	0.70	0.78	0.69	0.80
0.72	0.69	0.76	0.68	0.76	0.67	0.78
0.70	0.67	0.74	0.67	0.74	0.65	0.76
0.68	0.65	0.71	0.65	0.72	0.63	0.73
0.66	0.63	0.69	0.63	0.69	0.62	0.71
0.65	0.62	0.68	0.62	0.68	0.61	0.70

ARRI/ZEISS Master Anamorphic 2x MA 28/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	4		5.6		8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	6.40		4.54		3.22	
INF	6.40	INF	4.54	INF	3.22	INF
100	5.99	INF	4.31	INF	3.09	INF
50	5.66	INF	4.14	INF	3.00	INF
30	5.26	INF	3.92	INF	2.88	INF
20	4.84	INF	3.68	INF	2.75	INF
15	4.48	INF	3.47	INF	2.63	INF
12	4.17	INF	3.28	INF	2.52	INF
10	3.90	INF	3.11	INF	2.42	INF
8.0	3.55	INF	2.89	INF	2.29	INF
7.0	3.34	INF	2.75	INF	2.20	INF
6.0	3.10	95.12	2.58	INF	2.09	INF
5.0	2.81	22.73	2.38	INF	1.95	INF
4.5	2.65	15.08	2.26	576.04	1.87	INF
4.0	2.46	10.61	2.13	33.68	1.78	INF
3.5	2.27	7.69	1.98	15.24	1.68	INF
3.0	2.05	5.62	1.81	8.81	1.55	44.44
2.8	1.95	4.96	1.73	7.27	1.50	21.50
2.6	1.85	4.36	1.66	6.06	1.44	13.47
2.4	1.75	3.82	1.57	5.07	1.38	9.38
2.2	1.64	3.34	1.49	4.25	1.31	6.91
2.0	1.53	2.90	1.39	3.56	1.24	5.25
1.9	1.47	2.69	1.34	3.25	1.20	4.60
1.8	1.41	2.49	1.29	2.97	1.16	4.05
1.7	1.35	2.30	1.24	2.70	1.12	3.58
1.6	1.28	2.12	1.19	2.46	1.07	3.16
1.5	1.22	1.95	1.13	2.23	1.03	2.79
1.4	1.15	1.78	1.07	2.01	0.98	2.46
1.3	1.08	1.62	1.01	1.81	0.93	2.16
1.2	1.01	1.47	0.95	1.62	0.88	1.90
1.1	0.94	1.32	0.89	1.44	0.82	1.66
1.0	0.87	1.18	0.82	1.28	0.77	1.44
1.0	0.83	1.11	0.79	1.19	0.74	1.34
0.9	0.79	1.04	0.75	1.12	0.71	1.24
0.9	0.75	0.98	0.72	1.04	0.68	1.15
0.8	0.71	0.91	0.68	0.97	0.64	1.06
0.78	0.70	0.88	0.67	0.94	0.63	1.02
0.76	0.68	0.86	0.65	0.91	0.62	0.99
0.74	0.67	0.83	0.64	0.88	0.61	0.95
0.72	0.65	0.81	0.62	0.85	0.59	0.92
0.70	0.63	0.78	0.61	0.82	0.58	0.89
0.68	0.62	0.76	0.59	0.80	0.57	0.86
0.66	0.60	0.73	0.58	0.77	0.55	0.82
0.65	0.59	0.72	0.57	0.75	0.54	0.81

ARRI/ZEISS Master Anamorphic 2x MA 28/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	11		16		22	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	2.28		1.62		1.16	
INF	2.28	INF	1.62	INF	1.16	INF
100	2.20	INF	1.57	INF	1.12	INF
50	2.16	INF	1.55	INF	1.10	INF
30	2.10	INF	1.51	INF	1.09	INF
20	2.03	INF	1.48	INF	1.07	INF
15	1.96	INF	1.44	INF	1.05	INF
12	1.90	INF	1.41	INF	1.03	INF
10	1.84	INF	1.38	INF	1.02	INF
8.0	1.76	INF	1.33	INF	0.99	INF
7.0	1.71	INF	1.30	INF	0.97	INF
6.0	1.64	INF	1.26	INF	0.95	INF
5.0	1.56	INF	1.21	INF	0.92	INF
4.5	1.51	INF	1.18	INF	0.91	INF
4.0	1.45	INF	1.15	INF	0.88	INF
3.5	1.38	INF	1.10	INF	0.86	INF
3.0	1.29	INF	1.05	INF	0.83	INF
2.8	1.26	INF	1.02	INF	0.81	INF
2.6	1.21	INF	1.00	INF	0.79	INF
2.4	1.17	INF	0.96	INF	0.77	INF
2.2	1.12	60.68	0.93	INF	0.75	INF
2.0	1.07	16.00	0.89	INF	0.73	INF
1.9	1.04	11.22	0.87	INF	0.71	INF
1.8	1.01	8.42	0.85	INF	0.70	INF
1.7	0.98	6.59	0.83	INF	0.68	INF
1.6	0.94	5.29	0.81	117.67	0.67	INF
1.5	0.91	4.32	0.78	19.65	0.65	INF
1.4	0.87	3.58	0.75	10.06	0.63	INF
1.3	0.83	2.98	0.72	6.44	0.61	INF
1.2	0.79	2.50	0.69	4.54	0.59	INF
1.1	0.75	2.10	0.66	3.36	0.56	22.56
1.0	0.70	1.76	0.62	2.56	0.54	7.27
1.0	0.67	1.61	0.60	2.25	0.52	5.22
0.9	0.65	1.47	0.58	1.99	0.51	3.98
0.9	0.62	1.34	0.56	1.76	0.49	3.14
0.8	0.60	1.22	0.54	1.55	0.48	2.54
0.78	0.59	1.17	0.53	1.48	0.47	2.34
0.76	0.57	1.13	0.52	1.41	0.46	2.17
0.74	0.56	1.08	0.51	1.34	0.45	2.01
0.72	0.55	1.04	0.50	1.27	0.45	1.87
0.70	0.54	1.00	0.49	1.21	0.44	1.73
0.68	0.53	0.96	0.48	1.15	0.43	1.61
0.66	0.52	0.92	0.47	1.09	0.42	1.50
0.65	0.51	0.90	0.47	1.07	0.42	1.45

ARRI/ZEISS Master Anamorphic 2x MA 35/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	1.9		2		2.8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	20.98		19.51		13.80	
INF	20.98	INF	19.51	INF	13.80	INF
100	17.32	INF	16.30	INF	12.11	INF
50	14.77	INF	14.02	INF	10.80	INF
30	12.34	INF	11.82	INF	9.45	INF
20	10.24	428.12	9.88	INF	8.16	INF
15	8.75	52.55	8.48	64.80	7.19	INF
12	7.64	27.99	7.43	31.13	6.42	91.59
10	6.78	19.08	6.62	20.48	5.80	36.20
8.0	5.80	12.91	5.68	13.54	5.07	18.98
7.0	5.25	10.49	5.16	10.90	4.65	14.17
6.0	4.67	8.39	4.59	8.65	4.19	10.59
5.5	4.36	7.44	4.30	7.65	3.94	9.12
5.0	4.04	6.55	3.98	6.71	3.68	7.82
4.5	3.71	5.72	3.66	5.84	3.40	6.66
4.0	3.36	4.93	3.32	5.02	3.11	5.62
3.5	3.00	4.19	2.97	4.26	2.80	4.68
3.2	2.78	3.77	2.75	3.82	2.60	4.16
3.0	2.63	3.50	2.60	3.54	2.47	3.82
2.8	2.47	3.23	2.45	3.26	2.33	3.50
2.6	2.32	2.96	2.30	2.99	2.19	3.20
2.4	2.16	2.71	2.14	2.73	2.05	2.90
2.3	2.08	2.58	2.06	2.60	1.98	2.75
2.2	1.99	2.45	1.98	2.48	1.90	2.61
2.1	1.91	2.33	1.90	2.35	1.83	2.47
2.0	1.83	2.21	1.82	2.22	1.75	2.33
1.9	1.75	2.09	1.73	2.10	1.67	2.20
1.8	1.66	1.97	1.65	1.98	1.60	2.07
1.7	1.58	1.85	1.57	1.86	1.52	1.93
1.6	1.49	1.73	1.48	1.74	1.44	1.81
1.5	1.40	1.61	1.40	1.62	1.36	1.68
1.4	1.31	1.50	1.31	1.51	1.27	1.55
1.3	1.23	1.38	1.22	1.39	1.19	1.43
1.2	1.14	1.27	1.13	1.28	1.11	1.31
1.1	1.05	1.16	1.04	1.16	1.02	1.19
1.0	0.96	1.05	0.95	1.05	0.94	1.08
0.95	0.91	0.99	0.91	1.00	0.89	1.02
0.90	0.86	0.94	0.86	0.94	0.85	0.96
0.85	0.82	0.88	0.82	0.89	0.80	0.90
0.80	0.77	0.83	0.77	0.83	0.76	0.85
0.78	0.75	0.81	0.75	0.81	0.74	0.83
0.76	0.74	0.79	0.73	0.79	0.72	0.80
0.75	0.73	0.78	0.72	0.78	0.71	0.79

ARRI/ZEISS Master Anamorphic 2x MA 35/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	4		5.6		8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	9.77		6.92		4.90	
INF	9.77	INF	6.92	INF	4.90	INF
100	8.88	INF	6.44	INF	4.64	INF
50	8.15	INF	6.06	INF	4.44	INF
30	7.36	INF	5.61	INF	4.19	INF
20	6.56	INF	5.13	INF	3.92	INF
15	5.91	INF	4.73	INF	3.68	INF
12	5.38	INF	4.38	INF	3.47	INF
10	4.94	INF	4.09	INF	3.28	INF
8.0	4.40	43.98	3.71	INF	3.04	INF
7.0	4.08	24.59	3.48	INF	2.88	INF
6.0	3.72	15.49	3.22	44.92	2.70	INF
5.5	3.52	12.54	3.07	26.67	2.59	INF
5.0	3.31	10.20	2.91	17.93	2.48	INF
4.5	3.09	8.31	2.73	12.80	2.35	54.34
4.0	2.84	6.75	2.54	9.43	2.20	21.56
3.5	2.58	5.43	2.33	7.05	2.05	12.14
3.2	2.42	4.74	2.19	5.92	1.94	9.15
3.0	2.30	4.31	2.10	5.27	1.86	7.67
2.8	2.18	3.91	2.00	4.68	1.79	6.48
2.6	2.06	3.53	1.89	4.14	1.70	5.50
2.4	1.93	3.17	1.79	3.66	1.62	4.67
2.3	1.87	3.00	1.73	3.43	1.57	4.30
2.2	1.80	2.83	1.67	3.21	1.52	3.96
2.1	1.73	2.67	1.62	3.00	1.48	3.65
2.0	1.66	2.51	1.56	2.80	1.43	3.35
1.9	1.60	2.35	1.50	2.61	1.37	3.08
1.8	1.52	2.20	1.43	2.42	1.32	2.82
1.7	1.45	2.05	1.37	2.24	1.27	2.58
1.6	1.38	1.91	1.30	2.07	1.21	2.36
1.5	1.30	1.77	1.24	1.91	1.15	2.15
1.4	1.23	1.63	1.17	1.75	1.09	1.95
1.3	1.15	1.49	1.10	1.59	1.03	1.76
1.2	1.07	1.36	1.03	1.44	0.97	1.58
1.1	0.99	1.24	0.95	1.30	0.90	1.41
1.0	0.91	1.11	0.88	1.16	0.84	1.25
0.95	0.87	1.05	0.84	1.10	0.80	1.17
0.90	0.83	0.99	0.80	1.03	0.76	1.09
0.85	0.78	0.93	0.76	0.96	0.73	1.02
0.80	0.74	0.87	0.72	0.90	0.69	0.95
0.78	0.73	0.85	0.70	0.88	0.68	0.92
0.76	0.71	0.82	0.69	0.85	0.66	0.89
0.75	0.70	0.81	0.68	0.84	0.65	0.88

ARRI/ZEISS Master Anamorphic 2x MA 35/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	11		16		22	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	3.48		2.47		1.76	
INF	3.48	INF	2.47	INF	1.76	INF
100	3.33	INF	2.38	INF	1.69	INF
50	3.22	INF	2.32	INF	1.67	INF
30	3.09	INF	2.25	INF	1.63	INF
20	2.94	INF	2.17	INF	1.59	INF
15	2.81	INF	2.10	INF	1.55	INF
12	2.68	INF	2.03	INF	1.51	INF
10	2.57	INF	1.96	INF	1.47	INF
8.0	2.41	INF	1.87	INF	1.42	INF
7.0	2.32	INF	1.81	INF	1.39	INF
6.0	2.20	INF	1.74	INF	1.34	INF
5.5	2.13	INF	1.70	INF	1.32	INF
5.0	2.05	INF	1.65	INF	1.29	INF
4.5	1.96	INF	1.59	INF	1.25	INF
4.0	1.86	INF	1.52	INF	1.21	INF
3.5	1.74	INF	1.44	INF	1.16	INF
3.2	1.67	39.73	1.39	INF	1.13	INF
3.0	1.61	21.64	1.35	INF	1.10	INF
2.8	1.55	14.23	1.31	INF	1.07	INF
2.6	1.49	10.20	1.27	INF	1.04	INF
2.4	1.42	7.67	1.22	84.59	1.01	INF
2.3	1.39	6.73	1.19	33.12	0.99	INF
2.2	1.35	5.93	1.16	19.90	0.97	INF
2.1	1.31	5.25	1.14	13.85	0.96	INF
2.0	1.27	4.66	1.11	10.38	0.93	INF
1.9	1.23	4.15	1.08	8.13	0.91	INF
1.8	1.19	3.69	1.04	6.55	0.89	INF
1.7	1.15	3.29	1.01	5.38	0.86	52.12
1.6	1.10	2.93	0.97	4.48	0.84	17.64
1.5	1.05	2.61	0.94	3.77	0.81	10.08
1.4	1.00	2.32	0.90	3.19	0.78	6.77
1.3	0.95	2.06	0.86	2.71	0.75	4.91
1.2	0.90	1.81	0.81	2.30	0.72	3.71
1.1	0.84	1.59	0.77	1.96	0.68	2.89
1.0	0.78	1.39	0.72	1.66	0.64	2.28
0.95	0.75	1.29	0.69	1.52	0.62	2.03
0.90	0.72	1.20	0.66	1.40	0.60	1.81
0.85	0.69	1.11	0.64	1.28	0.58	1.62
0.80	0.66	1.03	0.61	1.17	0.55	1.44
0.78	0.64	1.00	0.60	1.12	0.54	1.38
0.76	0.63	0.96	0.59	1.08	0.54	1.31
0.75	0.62	0.95	0.58	1.06	0.53	1.28

ARRI/ZEISS Master Anamorphic 2x MA 40/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	1.9		2		2.8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	27.26		25.39		17.96	
INF	27.26	INF	25.39	INF	17.96	INF
100	21.40	INF	20.23	INF	15.20	INF
50	17.63	INF	16.83	INF	13.20	INF
30	14.28	INF	13.75	INF	11.23	INF
20	11.54	75.02	11.19	94.10	9.46	INF
15	9.68	33.31	9.43	36.60	8.18	90.72
12	8.34	21.41	8.15	22.72	7.20	36.07
10	7.32	15.77	7.18	16.47	6.43	22.51
8.0	6.19	11.31	6.09	11.66	5.54	14.39
7.0	5.57	9.41	5.49	9.65	5.04	11.44
6.0	4.92	7.68	4.86	7.84	4.50	8.99
5.0	4.23	6.11	4.18	6.22	3.92	6.91
4.5	3.87	5.38	3.83	5.46	3.60	5.99
4.0	3.49	4.68	3.46	4.74	3.28	5.13
3.5	3.11	4.01	3.08	4.05	2.93	4.34
3.0	2.71	3.37	2.69	3.40	2.58	3.59
2.8	2.54	3.12	2.53	3.14	2.43	3.31
2.6	2.38	2.87	2.36	2.89	2.28	3.03
2.4	2.21	2.63	2.20	2.65	2.12	2.76
2.2	2.04	2.39	2.03	2.41	1.96	2.50
2.0	1.87	2.16	1.86	2.17	1.80	2.25
1.9	1.78	2.04	1.77	2.05	1.72	2.12
1.8	1.69	1.92	1.68	1.93	1.64	2.00
1.7	1.60	1.81	1.60	1.82	1.56	1.87
1.6	1.51	1.70	1.51	1.71	1.47	1.75
1.5	1.42	1.59	1.42	1.59	1.39	1.63
1.4	1.33	1.47	1.33	1.48	1.30	1.52
1.3	1.24	1.36	1.24	1.37	1.22	1.40
1.2	1.15	1.25	1.15	1.26	1.13	1.28
1.1	1.06	1.15	1.06	1.15	1.04	1.17
1.0	0.97	1.04	0.96	1.04	0.95	1.06
1.0	0.92	0.98	0.92	0.99	0.90	1.00
0.90	0.87	0.93	0.87	0.93	0.86	0.95
0.85	0.83	0.88	0.82	0.88	0.81	0.89
0.80	0.78	0.82	0.78	0.83	0.77	0.84
0.78	0.76	0.80	0.76	0.80	0.75	0.81
0.76	0.74	0.78	0.74	0.78	0.73	0.79
0.74	0.72	0.76	0.72	0.76	0.71	0.77
0.72	0.70	0.74	0.70	0.74	0.69	0.75
0.70	0.68	0.72	0.68	0.72	0.68	0.73

ARRI/ZEISS Master Anamorphic 2x MA 40/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	4		5.6		8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	12.71		9.00		6.38	
INF	12.71	INF	9.00	INF	6.38	INF
100	11.25	INF	8.23	INF	5.96	INF
50	10.12	INF	7.61	INF	5.63	INF
30	8.92	INF	6.91	INF	5.24	INF
20	7.77	INF	6.20	INF	4.82	INF
15	6.88	INF	5.62	INF	4.46	INF
12	6.17	213.05	5.14	INF	4.16	INF
10	5.60	46.70	4.74	INF	3.89	INF
8.0	4.91	21.51	4.24	71.57	3.55	INF
7.0	4.52	15.53	3.94	31.34	3.34	INF
6.0	4.08	11.33	3.60	17.91	3.09	100.87
5.0	3.59	8.22	3.22	11.20	2.81	23.01
4.5	3.33	6.94	3.01	8.96	2.64	15.19
4.0	3.05	5.82	2.77	7.17	2.46	10.66
3.5	2.75	4.81	2.53	5.70	2.26	7.71
3.0	2.43	3.91	2.26	4.48	2.05	5.63
2.8	2.30	3.58	2.14	4.05	1.95	4.96
2.6	2.16	3.26	2.02	3.64	1.85	4.36
2.4	2.02	2.95	1.90	3.26	1.75	3.82
2.2	1.88	2.65	1.77	2.90	1.64	3.34
2.0	1.73	2.37	1.64	2.56	1.53	2.90
1.9	1.66	2.23	1.57	2.40	1.47	2.69
1.8	1.58	2.09	1.51	2.24	1.41	2.49
1.7	1.50	1.96	1.43	2.09	1.35	2.30
1.6	1.43	1.83	1.36	1.94	1.28	2.12
1.5	1.35	1.70	1.29	1.79	1.22	1.95
1.4	1.26	1.57	1.22	1.65	1.15	1.78
1.3	1.18	1.44	1.14	1.51	1.08	1.62
1.2	1.10	1.32	1.06	1.38	1.01	1.47
1.1	1.02	1.20	0.98	1.25	0.94	1.32
1.0	0.93	1.08	0.90	1.12	0.87	1.18
1.0	0.89	1.02	0.86	1.06	0.83	1.11
0.90	0.84	0.97	0.82	1.00	0.79	1.04
0.85	0.80	0.91	0.78	0.93	0.75	0.98
0.80	0.76	0.85	0.74	0.87	0.71	0.91
0.78	0.74	0.83	0.72	0.85	0.70	0.88
0.76	0.72	0.81	0.70	0.83	0.68	0.86
0.74	0.70	0.78	0.69	0.80	0.67	0.83
0.72	0.68	0.76	0.67	0.78	0.65	0.81
0.70	0.67	0.74	0.65	0.76	0.63	0.78

ARRI/ZEISS Master Anamorphic 2x MA 40/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	11		16		22	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	4.52		3.21		2.28	
INF	4.52	INF	3.21	INF	2.28	INF
100	4.29	INF	3.07	INF	2.19	INF
50	4.12	INF	2.98	INF	2.15	INF
30	3.90	INF	2.87	INF	2.09	INF
20	3.67	INF	2.74	INF	2.02	INF
15	3.46	INF	2.62	INF	1.95	INF
12	3.27	INF	2.51	INF	1.89	INF
10	3.10	INF	2.41	INF	1.84	INF
8.0	2.88	INF	2.28	INF	1.76	INF
7.0	2.74	INF	2.19	INF	1.71	INF
6.0	2.58	INF	2.08	INF	1.64	INF
5.0	2.37	INF	1.95	INF	1.56	INF
4.5	2.26	965.79	1.87	INF	1.51	INF
4.0	2.12	34.41	1.78	INF	1.45	INF
3.5	1.98	15.36	1.67	INF	1.38	INF
3.0	1.81	8.84	1.55	45.60	1.29	INF
2.8	1.73	7.29	1.50	21.72	1.26	INF
2.6	1.66	6.07	1.44	13.54	1.21	INF
2.4	1.57	5.07	1.38	9.41	1.17	INF
2.2	1.48	4.25	1.31	6.91	1.12	61.28
2.0	1.39	3.56	1.24	5.24	1.07	15.98
1.9	1.34	3.25	1.20	4.60	1.04	11.19
1.8	1.29	2.96	1.16	4.05	1.01	8.39
1.7	1.24	2.70	1.12	3.57	0.98	6.56
1.6	1.19	2.46	1.07	3.15	0.94	5.27
1.5	1.13	2.23	1.03	2.78	0.91	4.31
1.4	1.07	2.01	0.98	2.45	0.87	3.56
1.3	1.02	1.81	0.93	2.16	0.83	2.97
1.2	0.95	1.62	0.88	1.89	0.79	2.49
1.1	0.89	1.44	0.82	1.65	0.75	2.09
1.0	0.82	1.27	0.77	1.44	0.70	1.75
1.0	0.79	1.19	0.74	1.33	0.68	1.60
0.90	0.76	1.11	0.71	1.24	0.65	1.46
0.85	0.72	1.04	0.68	1.14	0.62	1.33
0.80	0.68	0.96	0.65	1.05	0.60	1.21
0.78	0.67	0.93	0.63	1.02	0.59	1.17
0.76	0.66	0.91	0.62	0.98	0.58	1.12
0.74	0.64	0.88	0.61	0.95	0.56	1.08
0.72	0.63	0.85	0.59	0.92	0.55	1.03
0.70	0.61	0.82	0.58	0.88	0.54	0.99

ARRI/ZEISS Master Anamorphic 2x MA 50/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	1.9		2		2.8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	41.70		38.81		27.46	
INF	41.70	INF	38.81	INF	27.46	INF
100	29.41	INF	27.94	INF	21.52	INF
50	22.73	INF	21.85	INF	17.71	INF
30	17.45	106.83	16.92	132.00	14.34	INF
20	13.52	38.39	13.20	41.21	11.58	73.51
15	11.04	23.40	10.83	24.42	9.71	33.00
12	9.32	16.83	9.17	17.35	8.36	21.28
10	8.07	13.14	7.96	13.45	7.34	15.70
8.0	6.72	9.89	6.64	10.06	6.20	11.27
7.0	6.00	8.40	5.94	8.53	5.58	9.38
6.0	5.25	7.00	5.20	7.09	4.93	7.66
5.0	4.47	5.67	4.43	5.73	4.24	6.10
4.5	4.07	5.04	4.04	5.08	3.87	5.37
4.0	3.65	4.42	3.63	4.45	3.50	4.67
3.5	3.23	3.82	3.21	3.84	3.11	4.00
3.0	2.80	3.23	2.79	3.25	2.71	3.36
2.8	2.63	3.00	2.61	3.01	2.55	3.11
2.6	2.45	2.77	2.44	2.78	2.38	2.87
2.4	2.27	2.54	2.26	2.56	2.21	2.63
2.2	2.09	2.32	2.08	2.33	2.04	2.39
2.0	1.91	2.10	1.90	2.11	1.87	2.15
1.9	1.82	1.99	1.81	2.00	1.78	2.04
1.8	1.73	1.88	1.72	1.89	1.69	1.92
1.7	1.64	1.77	1.63	1.78	1.60	1.81
1.6	1.54	1.66	1.54	1.67	1.51	1.70
1.5	1.45	1.55	1.45	1.56	1.43	1.58
1.4	1.36	1.45	1.35	1.45	1.33	1.47
1.3	1.26	1.34	1.26	1.34	1.24	1.36
1.2	1.17	1.23	1.17	1.24	1.15	1.25
1.1	1.07	1.13	1.07	1.13	1.06	1.14
1.0	0.98	1.02	0.98	1.03	0.97	1.04
0.95	0.93	0.97	0.93	0.97	0.92	0.98
0.90	0.88	0.92	0.88	0.92	0.87	0.93
0.85	0.83	0.87	0.83	0.87	0.83	0.88
0.80	0.79	0.82	0.79	0.82	0.78	0.82
0.75	0.74	0.76	0.74	0.76	0.73	0.77

ARRI/ZEISS Master Anamorphic 2x MA 50/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	4		5.6		8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	19.43		13.75		9.74	
INF	19.43	INF	13.75	INF	9.74	INF
100	16.24	INF	12.06	INF	8.84	INF
50	13.98	INF	10.76	INF	8.12	INF
30	11.79	INF	9.42	INF	7.33	INF
20	9.86	INF	8.14	INF	6.54	INF
15	8.47	65.63	7.17	INF	5.90	INF
12	7.42	31.30	6.41	93.79	5.37	INF
10	6.61	20.55	5.79	36.51	4.93	INF
8.0	5.67	13.57	5.06	19.06	4.39	44.56
7.0	5.15	10.91	4.64	14.20	4.08	24.76
6.0	4.59	8.66	4.18	10.61	3.72	15.55
5.0	3.98	6.72	3.67	7.83	3.31	10.22
4.5	3.66	5.84	3.40	6.66	3.08	8.32
4.0	3.32	5.02	3.11	5.62	2.84	6.75
3.5	2.97	4.26	2.80	4.68	2.58	5.44
3.0	2.60	3.54	2.47	3.82	2.30	4.31
2.8	2.45	3.26	2.33	3.50	2.18	3.91
2.6	2.30	2.99	2.19	3.19	2.06	3.53
2.4	2.14	2.73	2.05	2.90	1.93	3.17
2.2	1.98	2.48	1.90	2.61	1.80	2.83
2.0	1.82	2.22	1.75	2.33	1.67	2.50
1.9	1.73	2.10	1.67	2.20	1.60	2.35
1.8	1.65	1.98	1.60	2.06	1.53	2.20
1.7	1.57	1.86	1.52	1.93	1.45	2.05
1.6	1.48	1.74	1.44	1.80	1.38	1.91
1.5	1.40	1.62	1.36	1.68	1.31	1.76
1.4	1.31	1.51	1.27	1.55	1.23	1.63
1.3	1.22	1.39	1.19	1.43	1.15	1.49
1.2	1.13	1.28	1.11	1.31	1.07	1.36
1.1	1.04	1.16	1.02	1.19	0.99	1.23
1.0	0.95	1.05	0.94	1.07	0.91	1.11
0.95	0.91	1.00	0.89	1.02	0.87	1.05
0.90	0.86	0.94	0.85	0.96	0.83	0.99
0.85	0.82	0.89	0.80	0.90	0.79	0.93
0.80	0.77	0.83	0.76	0.85	0.74	0.87
0.75	0.72	0.78	0.71	0.79	0.70	0.81

ARRI/ZEISS Master Anamorphic 2x MA 50/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	11		16		22	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	6.90		4.90		3.48	
INF	6.90	INF	4.90	INF	3.48	INF
100	6.42	INF	4.62	INF	3.31	INF
50	6.03	INF	4.42	INF	3.21	INF
30	5.59	INF	4.18	INF	3.08	INF
20	5.11	INF	3.91	INF	2.93	INF
15	4.71	INF	3.67	INF	2.80	INF
12	4.37	INF	3.46	INF	2.67	INF
10	4.08	INF	3.28	INF	2.56	INF
8.0	3.70	INF	3.03	INF	2.41	INF
7.0	3.48	INF	2.88	INF	2.31	INF
6.0	3.21	45.60	2.69	INF	2.19	INF
5.0	2.90	18.02	2.47	INF	2.05	INF
4.5	2.73	12.84	2.35	55.22	1.96	INF
4.0	2.54	9.45	2.20	21.66	1.86	INF
3.5	2.33	7.05	2.04	12.16	1.74	INF
3.0	2.10	5.27	1.87	7.67	1.61	21.60
2.8	2.00	4.68	1.79	6.48	1.55	14.19
2.6	1.90	4.14	1.70	5.49	1.49	10.17
2.4	1.79	3.65	1.62	4.66	1.42	7.64
2.2	1.68	3.21	1.52	3.96	1.35	5.91
2.0	1.56	2.80	1.43	3.35	1.28	4.64
1.9	1.50	2.60	1.38	3.07	1.23	4.13
1.8	1.43	2.42	1.32	2.82	1.19	3.68
1.7	1.37	2.24	1.27	2.58	1.15	3.28
1.6	1.31	2.07	1.21	2.35	1.10	2.92
1.5	1.24	1.90	1.15	2.14	1.05	2.60
1.4	1.17	1.74	1.10	1.94	1.00	2.31
1.3	1.10	1.59	1.03	1.75	0.95	2.05
1.2	1.03	1.44	0.97	1.57	0.90	1.81
1.1	0.95	1.30	0.90	1.40	0.84	1.59
1.0	0.88	1.16	0.84	1.24	0.78	1.38
0.95	0.84	1.09	0.80	1.17	0.75	1.29
0.90	0.80	1.03	0.77	1.09	0.72	1.20
0.85	0.76	0.96	0.73	1.02	0.69	1.11
0.80	0.72	0.90	0.69	0.95	0.66	1.02
0.75	0.68	0.84	0.66	0.88	0.62	0.94

ARRI/ZEISS Master Anamorphic 2x MA 60/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	1.9		2		2.8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	58.70		54.74		38.72	
INF	58.70	INF	54.74	INF	38.72	INF
100	36.98	INF	35.36	INF	27.90	INF
50	27.00	336.92	26.13	577.12	21.82	INF
30	19.86	61.29	19.39	66.31	16.91	132.98
20	14.93	30.30	14.66	31.48	13.20	41.30
15	11.95	20.13	11.78	20.64	10.82	24.45
12	9.97	15.07	9.85	15.35	9.17	17.36
10	8.55	12.04	8.46	12.22	7.96	13.46
8.0	7.05	9.25	6.99	9.36	6.64	10.07
7.0	6.26	7.94	6.21	8.02	5.94	8.53
6.0	5.45	6.68	5.41	6.73	5.20	7.09
5.5	5.03	6.06	5.00	6.11	4.82	6.40
5.0	4.61	5.46	4.59	5.50	4.43	5.73
4.5	4.18	4.87	4.16	4.90	4.04	5.08
4.0	3.75	4.29	3.73	4.31	3.63	4.45
3.5	3.31	3.72	3.29	3.74	3.21	3.84
3.0	2.86	3.16	2.85	3.17	2.79	3.25
2.8	2.68	2.94	2.67	2.95	2.62	3.01
2.6	2.49	2.72	2.49	2.73	2.44	2.78
2.5	2.40	2.61	2.39	2.62	2.35	2.67
2.4	2.31	2.50	2.30	2.51	2.26	2.56
2.3	2.22	2.39	2.21	2.40	2.17	2.44
2.2	2.12	2.28	2.12	2.29	2.09	2.33
2.1	2.03	2.18	2.02	2.18	2.00	2.22
2.0	1.94	2.07	1.93	2.07	1.90	2.11
1.9	1.84	1.96	1.84	1.97	1.81	2.00
1.8	1.75	1.86	1.74	1.86	1.72	1.89
1.7	1.65	1.75	1.65	1.75	1.63	1.78
1.6	1.56	1.64	1.56	1.65	1.54	1.67
1.5	1.46	1.54	1.46	1.54	1.45	1.56
1.4	1.37	1.43	1.37	1.44	1.35	1.45
1.3	1.27	1.33	1.27	1.33	1.26	1.34
1.2	1.18	1.22	1.18	1.23	1.17	1.24
1.1	1.08	1.12	1.08	1.12	1.07	1.13
1.0	0.98	1.02	0.98	1.02	0.98	1.03
0.95	0.94	0.97	0.94	0.97	0.93	0.97
0.90	0.89	0.91	0.89	0.91	0.88	0.92

ARRI/ZEISS Master Anamorphic 2x MA 60/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	4		5.6		8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	27.40		19.39		13.73	
INF	27.40	INF	19.39	INF	13.73	INF
100	21.48	INF	16.21	INF	12.03	INF
50	17.69	INF	13.95	INF	10.75	INF
30	14.32	INF	11.77	INF	9.40	INF
20	11.57	73.90	9.85	INF	8.13	INF
15	9.70	33.08	8.46	66.03	7.17	INF
12	8.35	21.31	7.42	31.39	6.41	94.86
10	7.33	15.71	6.60	20.58	5.79	36.65
8.0	6.20	11.27	5.67	13.58	5.06	19.09
7.0	5.58	9.38	5.15	10.92	4.64	14.22
6.0	4.93	7.67	4.59	8.66	4.18	10.61
5.5	4.59	6.87	4.29	7.65	3.93	9.14
5.0	4.24	6.10	3.98	6.72	3.67	7.83
4.5	3.87	5.37	3.66	5.84	3.40	6.67
4.0	3.50	4.67	3.32	5.02	3.11	5.62
3.5	3.11	4.00	2.97	4.26	2.80	4.68
3.0	2.71	3.36	2.60	3.54	2.47	3.82
2.8	2.55	3.11	2.45	3.26	2.33	3.50
2.6	2.38	2.87	2.30	2.99	2.19	3.19
2.5	2.30	2.75	2.22	2.86	2.12	3.04
2.4	2.21	2.63	2.14	2.73	2.05	2.90
2.3	2.13	2.51	2.06	2.60	1.98	2.75
2.2	2.04	2.39	1.98	2.47	1.90	2.61
2.1	1.95	2.27	1.90	2.35	1.83	2.47
2.0	1.87	2.15	1.82	2.22	1.75	2.33
1.9	1.78	2.04	1.74	2.10	1.68	2.20
1.8	1.69	1.92	1.65	1.98	1.60	2.06
1.7	1.60	1.81	1.57	1.86	1.52	1.93
1.6	1.52	1.70	1.48	1.74	1.44	1.80
1.5	1.43	1.58	1.40	1.62	1.36	1.68
1.4	1.34	1.47	1.31	1.50	1.28	1.55
1.3	1.24	1.36	1.22	1.39	1.19	1.43
1.2	1.15	1.25	1.13	1.28	1.11	1.31
1.1	1.06	1.14	1.04	1.16	1.02	1.19
1.0	0.97	1.04	0.95	1.05	0.94	1.07
0.95	0.92	0.98	0.91	1.00	0.89	1.02
0.90	0.87	0.93	0.86	0.94	0.85	0.96

ARRI/ZEISS Master Anamorphic 2x MA 60/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	11		16		22	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	9.73		6.90		4.89	
INF	9.73	INF	6.90	INF	4.89	INF
100	8.82	INF	6.40	INF	4.61	INF
50	8.11	INF	6.02	INF	4.41	INF
30	7.32	INF	5.58	INF	4.17	INF
20	6.53	INF	5.11	INF	3.90	INF
15	5.89	INF	4.71	INF	3.67	INF
12	5.37	INF	4.37	INF	3.46	INF
10	4.93	INF	4.07	INF	3.27	INF
8.0	4.39	44.81	3.70	INF	3.03	INF
7.0	4.07	24.82	3.47	INF	2.87	INF
6.0	3.72	15.57	3.21	45.84	2.69	INF
5.5	3.52	12.58	3.06	26.95	2.59	INF
5.0	3.31	10.23	2.90	18.04	2.47	INF
4.5	3.08	8.32	2.73	12.84	2.35	55.36
4.0	2.84	6.75	2.54	9.45	2.20	21.65
3.5	2.58	5.43	2.33	7.05	2.05	12.14
3.0	2.30	4.31	2.10	5.27	1.87	7.66
2.8	2.18	3.91	2.00	4.67	1.79	6.47
2.6	2.06	3.53	1.90	4.14	1.70	5.48
2.5	2.00	3.34	1.84	3.89	1.66	5.05
2.4	1.93	3.17	1.79	3.65	1.62	4.65
2.3	1.87	2.99	1.73	3.42	1.57	4.29
2.2	1.80	2.83	1.68	3.20	1.53	3.95
2.1	1.73	2.66	1.62	2.99	1.48	3.63
2.0	1.67	2.50	1.56	2.79	1.43	3.34
1.9	1.60	2.35	1.50	2.60	1.38	3.07
1.8	1.53	2.20	1.44	2.42	1.32	2.81
1.7	1.45	2.05	1.37	2.24	1.27	2.57
1.6	1.38	1.90	1.31	2.07	1.21	2.35
1.5	1.31	1.76	1.24	1.90	1.16	2.14
1.4	1.23	1.63	1.17	1.74	1.10	1.94
1.3	1.15	1.49	1.10	1.59	1.04	1.75
1.2	1.07	1.36	1.03	1.44	0.97	1.57
1.1	0.99	1.23	0.96	1.30	0.91	1.40
1.0	0.91	1.11	0.88	1.16	0.84	1.24
0.95	0.87	1.05	0.84	1.09	0.80	1.16
0.90	0.83	0.99	0.80	1.03	0.77	1.09

ARRI/ZEISS Master Anamorphic 2x MA 75/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	1.9		2		2.8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	89.07		82.80		58.57	
INF	89.07	INF	82.80	INF	58.57	INF
100	47.11	INF	45.29	INF	36.92	INF
50	32.03	113.89	31.18	126.11	26.98	341.35
30	22.45	45.20	22.03	47.00	19.85	61.43
20	16.34	25.77	16.12	26.35	14.92	30.33
15	12.85	18.02	12.71	18.30	11.95	20.14
12	10.58	13.86	10.49	14.02	9.97	15.07
10	9.00	11.26	8.93	11.36	8.55	12.04
9.0	8.18	10.00	8.12	10.09	7.81	10.62
8.0	7.35	8.78	7.30	8.85	7.05	9.25
7.0	6.50	7.59	6.46	7.64	6.26	7.94
6.0	5.63	6.43	5.60	6.46	5.45	6.68
5.5	5.18	5.86	5.16	5.89	5.03	6.06
5.0	4.74	5.29	4.72	5.32	4.61	5.46
4.5	4.29	4.74	4.27	4.75	4.18	4.87
4.0	3.83	4.19	3.82	4.20	3.75	4.29
3.8	3.65	3.97	3.64	3.98	3.57	4.06
3.6	3.46	3.75	3.45	3.76	3.40	3.83
3.4	3.28	3.53	3.27	3.54	3.22	3.61
3.2	3.09	3.32	3.08	3.33	3.04	3.38
3.0	2.91	3.10	2.90	3.11	2.86	3.16
2.8	2.72	2.89	2.71	2.90	2.68	2.94
2.6	2.53	2.68	2.52	2.68	2.49	2.72
2.5	2.43	2.57	2.43	2.58	2.40	2.61
2.4	2.34	2.46	2.33	2.47	2.31	2.50
2.3	2.24	2.36	2.24	2.36	2.22	2.39
2.2	2.15	2.25	2.15	2.26	2.12	2.28
2.1	2.05	2.15	2.05	2.15	2.03	2.18
2.0	1.96	2.04	1.96	2.05	1.94	2.07
1.9	1.86	1.94	1.86	1.94	1.84	1.96
1.8	1.77	1.84	1.76	1.84	1.75	1.86
1.7	1.67	1.73	1.67	1.73	1.65	1.75
1.6	1.57	1.63	1.57	1.63	1.56	1.64
1.5	1.48	1.52	1.48	1.53	1.46	1.54
1.4	1.38	1.42	1.38	1.42	1.37	1.43
1.3	1.28	1.32	1.28	1.32	1.27	1.33
1.2	1.19	1.22	1.18	1.22	1.18	1.22
1.1	1.09	1.11	1.09	1.11	1.08	1.12
1.0	0.99	1.01	0.99	1.01	0.98	1.02
0.95	0.94	0.96	0.94	0.96	0.94	0.96
0.90	0.89	0.91	0.89	0.91	0.89	0.91

ARRI/ZEISS Master Anamorphic 2x MA 75/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	4		5.6		8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	41.44		29.32		20.76	
INF	41.44	INF	29.32	INF	20.76	INF
100	29.28	INF	22.64	INF	17.15	INF
50	22.66	INF	18.47	INF	14.65	INF
30	17.41	108.50	14.83	INF	12.26	INF
20	13.50	38.59	11.90	62.75	10.19	547.55
15	11.02	23.47	9.93	30.63	8.71	53.90
12	9.31	16.86	8.52	20.26	7.61	28.34
10	8.07	13.16	7.47	15.14	6.76	19.23
9.0	7.40	11.48	6.90	12.95	6.29	15.83
8.0	6.71	9.90	6.29	10.97	5.78	12.97
7.0	6.00	8.41	5.66	9.17	5.24	10.52
6.0	5.25	7.00	4.99	7.52	4.66	8.41
5.5	4.86	6.33	4.64	6.75	4.36	7.46
5.0	4.47	5.68	4.28	6.01	4.04	6.56
4.5	4.07	5.04	3.91	5.30	3.71	5.73
4.0	3.65	4.42	3.53	4.62	3.36	4.94
3.8	3.49	4.18	3.37	4.36	3.22	4.64
3.6	3.32	3.94	3.21	4.09	3.08	4.34
3.4	3.15	3.70	3.05	3.84	2.93	4.05
3.2	2.98	3.46	2.89	3.58	2.78	3.77
3.0	2.80	3.23	2.73	3.33	2.63	3.49
2.8	2.63	3.00	2.56	3.09	2.47	3.23
2.6	2.45	2.77	2.39	2.85	2.32	2.96
2.5	2.36	2.66	2.31	2.73	2.24	2.83
2.4	2.27	2.54	2.22	2.61	2.16	2.70
2.3	2.18	2.43	2.14	2.49	2.08	2.58
2.2	2.09	2.32	2.05	2.37	2.00	2.45
2.1	2.00	2.21	1.96	2.26	1.91	2.33
2.0	1.91	2.10	1.88	2.14	1.83	2.21
1.9	1.82	1.99	1.79	2.03	1.75	2.08
1.8	1.73	1.88	1.70	1.91	1.66	1.96
1.7	1.64	1.77	1.61	1.80	1.58	1.85
1.6	1.54	1.66	1.52	1.69	1.49	1.73
1.5	1.45	1.55	1.43	1.58	1.40	1.61
1.4	1.36	1.45	1.34	1.47	1.32	1.50
1.3	1.26	1.34	1.25	1.36	1.23	1.38
1.2	1.17	1.23	1.16	1.25	1.14	1.27
1.1	1.07	1.13	1.06	1.14	1.05	1.16
1.0	0.98	1.02	0.97	1.03	0.96	1.05
0.95	0.93	0.97	0.92	0.98	0.91	0.99
0.90	0.88	0.92	0.88	0.93	0.87	0.94

ARRI/ZEISS Master Anamorphic 2x MA 75/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	11		16		22	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	14.70		10.42		7.39	
INF	14.70	INF	10.42	INF	7.39	INF
100	12.77	INF	9.38	INF	6.82	INF
50	11.33	INF	8.58	INF	6.39	INF
30	9.85	INF	7.70	INF	5.89	INF
20	8.47	INF	6.83	INF	5.37	INF
15	7.42	INF	6.14	INF	4.93	INF
12	6.61	65.04	5.57	INF	4.56	INF
10	5.96	31.13	5.10	249.05	4.24	INF
9.0	5.59	23.10	4.83	65.76	4.05	INF
8.0	5.19	17.47	4.53	34.25	3.84	INF
7.0	4.75	13.30	4.19	21.19	3.60	132.38
6.0	4.27	10.09	3.81	14.05	3.31	31.64
5.5	4.01	8.74	3.61	11.57	3.16	21.32
5.0	3.74	7.54	3.39	9.55	2.99	15.32
4.5	3.46	6.45	3.15	7.87	2.80	11.40
4.0	3.15	5.47	2.90	6.45	2.60	8.64
3.8	3.03	5.10	2.79	5.94	2.52	7.75
3.6	2.90	4.74	2.69	5.46	2.43	6.95
3.4	2.77	4.40	2.57	5.01	2.34	6.24
3.2	2.64	4.07	2.46	4.59	2.24	5.59
3.0	2.50	3.75	2.34	4.18	2.14	5.00
2.8	2.36	3.44	2.22	3.80	2.04	4.46
2.6	2.22	3.14	2.09	3.44	1.93	3.97
2.5	2.14	3.00	2.03	3.27	1.88	3.74
2.4	2.07	2.85	1.96	3.10	1.82	3.52
2.3	2.00	2.71	1.89	2.93	1.76	3.31
2.2	1.92	2.57	1.83	2.77	1.71	3.10
2.1	1.85	2.44	1.76	2.61	1.65	2.90
2.0	1.77	2.30	1.69	2.46	1.58	2.72
1.9	1.69	2.17	1.62	2.31	1.52	2.53
1.8	1.61	2.04	1.54	2.16	1.46	2.36
1.7	1.53	1.91	1.47	2.02	1.39	2.19
1.6	1.45	1.79	1.39	1.88	1.32	2.02
1.5	1.37	1.66	1.32	1.74	1.26	1.86
1.4	1.28	1.54	1.24	1.61	1.19	1.71
1.3	1.20	1.42	1.16	1.48	1.11	1.56
1.2	1.11	1.30	1.08	1.35	1.04	1.42
1.1	1.03	1.18	1.00	1.22	0.97	1.28
1.0	0.94	1.07	0.92	1.10	0.89	1.15
0.95	0.90	1.01	0.88	1.04	0.85	1.08
0.90	0.85	0.95	0.83	0.98	0.81	1.01

ARRI/ZEISS Master Anamorphic 2x MA 100/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	1.9		2		2.8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	151.00		140.65		99.48	
INF	151.00	INF	140.65	INF	99.48	INF
100	60.17	295.87	58.45	345.77	49.87	INF
50	37.58	74.70	36.90	77.52	33.29	100.42
30	25.04	37.41	24.74	38.11	23.06	42.91
20	17.67	23.04	17.52	23.30	16.66	25.01
15	13.65	16.64	13.56	16.78	13.04	17.65
12	11.12	13.03	11.06	13.11	10.72	13.63
10	9.38	10.70	9.34	10.76	9.09	11.11
8.0	7.60	8.44	7.57	8.48	7.41	8.69
7.0	6.69	7.34	6.67	7.36	6.55	7.52
6.0	5.77	6.24	5.76	6.26	5.66	6.38
5.5	5.31	5.70	5.30	5.72	5.22	5.82
5.0	4.84	5.17	4.83	5.18	4.77	5.26
4.5	4.37	4.64	4.36	4.65	4.31	4.71
4.0	3.90	4.11	3.89	4.11	3.85	4.16
3.8	3.71	3.90	3.70	3.90	3.66	3.95
3.6	3.52	3.69	3.51	3.69	3.48	3.73
3.4	3.33	3.48	3.32	3.48	3.29	3.52
3.2	3.14	3.27	3.13	3.27	3.10	3.30
3.0	2.94	3.06	2.94	3.06	2.92	3.09
2.8	2.75	2.85	2.75	2.86	2.73	2.88
2.6	2.56	2.64	2.56	2.65	2.54	2.67
2.5	2.46	2.54	2.46	2.54	2.44	2.56
2.4	2.36	2.44	2.36	2.44	2.35	2.46
2.3	2.27	2.33	2.27	2.34	2.25	2.35
2.2	2.17	2.23	2.17	2.23	2.15	2.25
2.1	2.07	2.13	2.07	2.13	2.06	2.14
2.0	1.98	2.03	1.97	2.03	1.96	2.04
1.9	1.88	1.92	1.88	1.93	1.87	1.94
1.8	1.78	1.82	1.78	1.82	1.77	1.83
1.7	1.68	1.72	1.68	1.72	1.67	1.73
1.6	1.58	1.62	1.58	1.62	1.58	1.63
1.5	1.49	1.51	1.49	1.52	1.48	1.52
1.4	1.39	1.41	1.39	1.41	1.38	1.42
1.3	1.29	1.31	1.29	1.31	1.28	1.32
1.2	1.19	1.21	1.19	1.21	1.19	1.21
1.1	1.09	1.11	1.09	1.11	1.09	1.11
1.0	0.99	1.01	0.99	1.01	0.99	1.01
0.95	0.95	0.96	0.94	0.96	0.94	0.96

ARRI/ZEISS Master Anamorphic 2x MA 100/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	4		5.6		8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	70.37		49.79		35.24	
INF	70.37	INF	49.79	INF	35.24	INF
100	41.30	INF	33.22	INF	26.02	INF
50	29.24	172.46	24.95	INF	20.66	INF
30	21.05	52.22	18.73	75.32	16.21	201.28
20	15.59	27.90	14.28	33.36	12.77	46.12
15	12.38	19.04	11.54	21.42	10.53	26.04
12	10.26	14.45	9.68	15.78	8.96	18.15
10	8.77	11.64	8.34	12.49	7.80	13.92
8.0	7.19	9.01	6.90	9.51	6.53	10.32
7.0	6.37	7.76	6.15	8.13	5.85	8.71
6.0	5.54	6.55	5.36	6.81	5.14	7.21
5.5	5.11	5.96	4.96	6.17	4.77	6.50
5.0	4.67	5.38	4.55	5.55	4.39	5.81
4.5	4.24	4.80	4.13	4.94	4.00	5.14
4.0	3.79	4.24	3.71	4.34	3.60	4.50
3.8	3.61	4.01	3.54	4.11	3.44	4.25
3.6	3.43	3.79	3.36	3.87	3.27	4.00
3.4	3.25	3.57	3.19	3.64	3.11	3.75
3.2	3.07	3.35	3.01	3.41	2.94	3.51
3.0	2.88	3.13	2.84	3.19	2.77	3.27
2.8	2.70	2.91	2.66	2.96	2.60	3.03
2.6	2.51	2.70	2.48	2.74	2.43	2.80
2.5	2.42	2.59	2.39	2.63	2.34	2.68
2.4	2.32	2.48	2.29	2.52	2.25	2.57
2.3	2.23	2.37	2.20	2.41	2.16	2.45
2.2	2.14	2.27	2.11	2.30	2.08	2.34
2.1	2.04	2.16	2.02	2.19	1.99	2.23
2.0	1.95	2.06	1.93	2.08	1.90	2.11
1.9	1.85	1.95	1.83	1.97	1.81	2.00
1.8	1.76	1.85	1.74	1.86	1.72	1.89
1.7	1.66	1.74	1.65	1.76	1.63	1.78
1.6	1.57	1.64	1.55	1.65	1.53	1.67
1.5	1.47	1.53	1.46	1.54	1.44	1.56
1.4	1.38	1.43	1.36	1.44	1.35	1.45
1.3	1.28	1.32	1.27	1.33	1.26	1.35
1.2	1.18	1.22	1.17	1.23	1.16	1.24
1.1	1.09	1.12	1.08	1.12	1.07	1.13
1.0	0.99	1.01	0.98	1.02	0.98	1.03
0.95	0.94	0.96	0.93	0.97	0.93	0.97

ARRI/ZEISS Master Anamorphic 2x MA 100/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	11		16		22	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	24.95		17.67		12.52	
INF	24.95	INF	17.67	INF	12.52	INF
100	19.92	INF	14.96	INF	11.06	INF
50	16.62	INF	13.02	INF	9.97	INF
30	13.62	INF	11.10	INF	8.81	INF
20	11.11	100.48	9.38	INF	7.69	INF
15	9.38	37.47	8.12	98.75	6.82	INF
12	8.11	23.03	7.15	37.19	6.13	285.13
10	7.15	16.62	6.40	22.91	5.57	49.24
8.0	6.07	11.73	5.52	14.54	4.89	21.97
7.0	5.48	9.69	5.03	11.53	4.50	15.75
6.0	4.85	7.87	4.49	9.03	4.07	11.43
5.5	4.52	7.03	4.21	7.94	3.83	9.73
5.0	4.18	6.23	3.91	6.93	3.59	8.26
4.5	3.82	5.47	3.60	6.00	3.32	6.97
4.0	3.46	4.75	3.27	5.14	3.04	5.83
3.8	3.31	4.47	3.14	4.81	2.93	5.41
3.6	3.16	4.19	3.00	4.50	2.81	5.01
3.4	3.00	3.92	2.86	4.19	2.69	4.63
3.2	2.85	3.66	2.72	3.89	2.56	4.26
3.0	2.69	3.40	2.58	3.59	2.43	3.91
2.8	2.53	3.14	2.43	3.31	2.30	3.58
2.6	2.36	2.89	2.28	3.03	2.16	3.26
2.5	2.28	2.77	2.20	2.90	2.10	3.10
2.4	2.20	2.65	2.12	2.76	2.03	2.95
2.3	2.11	2.52	2.04	2.63	1.95	2.80
2.2	2.03	2.40	1.97	2.50	1.88	2.65
2.1	1.94	2.28	1.89	2.37	1.81	2.50
2.0	1.86	2.17	1.81	2.24	1.74	2.36
1.9	1.77	2.05	1.72	2.12	1.66	2.22
1.8	1.69	1.93	1.64	1.99	1.58	2.09
1.7	1.60	1.82	1.56	1.87	1.51	1.95
1.6	1.51	1.70	1.47	1.75	1.43	1.82
1.5	1.42	1.59	1.39	1.63	1.35	1.69
1.4	1.33	1.48	1.30	1.51	1.27	1.56
1.3	1.24	1.37	1.22	1.40	1.19	1.44
1.2	1.15	1.26	1.13	1.28	1.10	1.32
1.1	1.06	1.15	1.04	1.17	1.02	1.20
1.0	0.97	1.04	0.95	1.05	0.93	1.08
0.95	0.92	0.98	0.91	1.00	0.89	1.02

ARRI/ZEISS Master Anamorphic 2x MA 135/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	1.9		2		2.8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	288.04		269.01		190.26	
INF	288.04	INF	269.01	INF	190.26	INF
100	74.25	153.11	72.92	159.09	65.56	210.65
50	42.62	60.47	42.18	61.38	39.61	67.78
30	27.18	33.47	27.00	33.75	25.93	35.59
20	18.71	21.48	18.62	21.60	18.11	22.33
15	14.26	15.82	14.21	15.88	13.91	16.27
12	11.53	12.52	11.49	12.55	11.30	12.80
10	9.67	10.36	9.65	10.38	9.51	10.55
8.0	7.79	8.23	7.77	8.24	7.68	8.35
7.0	6.84	7.17	6.83	7.18	6.76	7.26
6.0	5.88	6.13	5.87	6.13	5.82	6.19
5.5	5.40	5.60	5.39	5.61	5.35	5.66
5.0	4.92	5.09	4.91	5.09	4.88	5.13
4.5	4.43	4.57	4.43	4.57	4.40	4.61
4.0	3.95	4.05	3.94	4.06	3.92	4.08
3.8	3.75	3.85	3.75	3.85	3.73	3.88
3.6	3.56	3.64	3.55	3.65	3.54	3.67
3.4	3.36	3.44	3.36	3.44	3.34	3.46
3.2	3.17	3.23	3.16	3.24	3.15	3.25
3.0	2.97	3.03	2.97	3.03	2.96	3.05
2.8	2.77	2.83	2.77	2.83	2.76	2.84
2.6	2.58	2.62	2.58	2.62	2.57	2.63
2.5	2.48	2.52	2.48	2.52	2.47	2.53
2.4	2.38	2.42	2.38	2.42	2.37	2.43
2.3	2.28	2.32	2.28	2.32	2.27	2.33
2.2	2.18	2.22	2.18	2.22	2.18	2.22
2.1	2.09	2.11	2.09	2.12	2.08	2.12
2.0	1.99	2.01	1.99	2.01	1.98	2.02
1.9	1.89	1.91	1.89	1.91	1.88	1.92
1.8	1.79	1.81	1.79	1.81	1.78	1.82
1.7	1.69	1.71	1.69	1.71	1.69	1.71
1.6	1.59	1.61	1.59	1.61	1.59	1.61
1.5	1.49	1.51	1.49	1.51	1.49	1.51
1.4	1.39	1.41	1.39	1.41	1.39	1.41
1.3	1.30	1.31	1.29	1.31	1.29	1.31
1.2	1.20	1.20	1.20	1.21	1.19	1.21

ARRI/ZEISS Master Anamorphic 2x MA 135/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	4		5.6		8	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	134.57		95.20		67.35	
INF	134.57	INF	95.20	INF	67.35	INF
100	57.38	388.87	48.77	INF	40.23	INF
50	36.47	79.48	32.80	105.17	28.71	193.68
30	24.55	38.57	22.83	43.74	20.77	53.99
20	17.43	23.47	16.54	25.28	15.44	28.39
15	13.51	16.87	12.97	17.78	12.28	19.26
12	11.03	13.16	10.67	13.71	10.20	14.57
10	9.32	10.79	9.06	11.16	8.72	11.72
8.0	7.56	8.50	7.39	8.72	7.16	9.06
7.0	6.66	7.38	6.53	7.55	6.35	7.80
6.0	5.75	6.27	5.65	6.40	5.52	6.57
5.5	5.29	5.73	5.21	5.83	5.09	5.98
5.0	4.83	5.19	4.76	5.27	4.66	5.39
4.5	4.36	4.65	4.30	4.72	4.23	4.81
4.0	3.89	4.12	3.84	4.17	3.78	4.24
3.8	3.70	3.91	3.66	3.95	3.60	4.02
3.6	3.51	3.70	3.47	3.74	3.42	3.80
3.4	3.32	3.49	3.29	3.52	3.24	3.57
3.2	3.13	3.28	3.10	3.31	3.06	3.35
3.0	2.94	3.07	2.91	3.09	2.88	3.13
2.8	2.75	2.86	2.72	2.88	2.69	2.92
2.6	2.55	2.65	2.53	2.67	2.51	2.70
2.5	2.46	2.55	2.44	2.56	2.42	2.59
2.4	2.36	2.44	2.34	2.46	2.32	2.48
2.3	2.26	2.34	2.25	2.35	2.23	2.38
2.2	2.17	2.23	2.15	2.25	2.13	2.27
2.1	2.07	2.13	2.06	2.14	2.04	2.16
2.0	1.97	2.03	1.96	2.04	1.95	2.06
1.9	1.88	1.93	1.87	1.94	1.85	1.95
1.8	1.78	1.82	1.77	1.83	1.76	1.85
1.7	1.68	1.72	1.67	1.73	1.66	1.74
1.6	1.58	1.62	1.58	1.63	1.57	1.64
1.5	1.49	1.52	1.48	1.52	1.47	1.53
1.4	1.39	1.41	1.38	1.42	1.37	1.43
1.3	1.29	1.31	1.28	1.32	1.28	1.32
1.2	1.19	1.21	1.19	1.21	1.18	1.22

ARRI/ZEISS Master Anamorphic 2x MA 135/T1.9 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	11		16		22	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	47.67		33.74		23.90	
INF	47.67	INF	33.74	INF	23.90	INF
100	32.25	INF	25.18	INF	19.22	INF
50	24.40	INF	20.13	INF	16.14	INF
30	18.42	80.72	15.89	269.30	13.29	INF
20	14.11	34.36	12.57	48.91	10.89	121.87
15	11.43	21.83	10.40	26.90	9.23	40.05
12	9.60	15.99	8.87	18.55	8.00	23.97
10	8.28	12.62	7.73	14.16	7.07	17.10
8.0	6.86	9.59	6.48	10.44	6.01	11.96
7.0	6.12	8.18	5.81	8.80	5.43	9.84
6.0	5.34	6.85	5.11	7.27	4.81	7.97
5.5	4.94	6.20	4.74	6.55	4.49	7.10
5.0	4.54	5.57	4.37	5.85	4.15	6.29
4.5	4.12	4.96	3.98	5.17	3.80	5.51
4.0	3.70	4.35	3.59	4.52	3.44	4.78
3.8	3.53	4.12	3.43	4.27	3.29	4.49
3.6	3.36	3.88	3.26	4.01	3.14	4.21
3.4	3.18	3.65	3.10	3.77	2.99	3.94
3.2	3.01	3.42	2.93	3.52	2.83	3.67
3.0	2.83	3.19	2.76	3.28	2.68	3.41
2.8	2.65	2.97	2.59	3.04	2.52	3.15
2.6	2.47	2.74	2.42	2.81	2.36	2.90
2.5	2.38	2.63	2.34	2.69	2.27	2.78
2.4	2.29	2.52	2.25	2.57	2.19	2.65
2.3	2.20	2.41	2.16	2.46	2.11	2.53
2.2	2.11	2.30	2.07	2.34	2.02	2.41
2.1	2.02	2.19	1.98	2.23	1.94	2.29
2.0	1.92	2.08	1.90	2.12	1.85	2.17
1.9	1.83	1.97	1.81	2.01	1.77	2.05
1.8	1.74	1.87	1.72	1.89	1.68	1.94
1.7	1.65	1.76	1.62	1.78	1.60	1.82
1.6	1.55	1.65	1.53	1.67	1.51	1.71
1.5	1.46	1.54	1.44	1.56	1.42	1.59
1.4	1.36	1.44	1.35	1.46	1.33	1.48
1.3	1.27	1.33	1.26	1.35	1.24	1.37
1.2	1.17	1.23	1.16	1.24	1.15	1.26

ARRI/ZEISS Master Anamorphic 2x MA 180/T2.8 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	2.8		4		5.6	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	347.39		238.99		169.04	
INF	347.39	INF	238.99	INF	169.04	INF
100	77.67	140.35	70.52	171.82	62.85	244.58
50	43.73	58.38	41.37	63.18	38.61	70.93
30	27.63	32.82	26.67	34.28	25.50	36.43
20	18.92	21.21	18.47	21.81	17.90	22.66
15	14.39	15.67	14.12	15.99	13.79	16.44
12	11.61	12.42	11.43	12.63	11.22	12.90
10	9.73	10.29	9.61	10.43	9.45	10.62
8.0	7.82	8.18	7.75	8.27	7.65	8.39
7.0	6.87	7.14	6.81	7.21	6.73	7.30
6.0	5.90	6.10	5.86	6.15	5.80	6.21
5.5	5.42	5.59	5.38	5.63	5.33	5.68
5.0	4.93	5.07	4.90	5.10	4.86	5.15
4.5	4.45	4.56	4.42	4.58	4.39	4.62
4.0	3.96	4.04	3.94	4.07	3.91	4.09
3.8	3.76	3.84	3.74	3.86	3.72	3.88
3.6	3.57	3.64	3.55	3.65	3.53	3.67
3.4	3.37	3.43	3.36	3.45	3.34	3.47
3.2	3.17	3.23	3.16	3.24	3.14	3.26
3.0	2.98	3.03	2.97	3.04	2.95	3.05
2.8	2.78	2.82	2.77	2.83	2.76	2.84
2.6	2.58	2.62	2.57	2.63	2.56	2.64
2.5	2.48	2.52	2.48	2.53	2.47	2.54
2.4	2.39	2.42	2.38	2.42	2.37	2.43
2.3	2.29	2.31	2.28	2.32	2.27	2.33
2.2	2.19	2.21	2.18	2.22	2.17	2.23
2.1	2.09	2.11	2.08	2.12	2.08	2.12
2.0	1.99	2.01	1.99	2.02	1.98	2.02
1.9	1.89	1.91	1.89	1.91	1.88	1.92
1.8	1.79	1.81	1.79	1.81	1.78	1.82
1.7	1.69	1.71	1.69	1.71	1.69	1.72
1.6	1.59	1.61	1.59	1.61	1.59	1.61
1.5	1.49	1.51	1.49	1.51	1.49	1.51

ARRI/ZEISS Master Anamorphic 2x MA 180/T2.8 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop					
	8		11		16	
m	von / from	bis / to	von / from	bis / to	von / from	bis / to
hyperfokale Distanz hyperfocal distance	119.58		84.61		59.88	
INF	119.58	INF	84.61	INF	59.88	INF
100	54.47	609.74	45.82	INF	37.43	INF
50	35.28	85.80	31.45	121.97	27.26	302.09
30	24.01	39.99	22.17	46.38	20.01	59.94
20	17.15	23.98	16.20	26.14	15.02	29.94
15	13.34	17.13	12.76	18.19	12.02	19.95
12	10.92	13.32	10.53	13.95	10.02	14.96
10	9.24	10.90	8.96	11.32	8.59	11.97
8.0	7.51	8.56	7.32	8.82	7.07	9.21
7.0	6.62	7.42	6.48	7.62	6.28	7.90
6.0	5.72	6.31	5.61	6.44	5.47	6.65
5.5	5.27	5.76	5.17	5.87	5.05	6.04
5.0	4.81	5.21	4.73	5.30	4.63	5.44
4.5	4.34	4.67	4.28	4.74	4.20	4.85
4.0	3.88	4.13	3.83	4.19	3.76	4.27
3.8	3.69	3.92	3.64	3.97	3.58	4.05
3.6	3.50	3.71	3.46	3.75	3.41	3.82
3.4	3.31	3.49	3.28	3.54	3.23	3.59
3.2	3.12	3.28	3.09	3.32	3.05	3.37
3.0	2.93	3.07	2.90	3.10	2.87	3.15
2.8	2.74	2.86	2.72	2.89	2.68	2.93
2.6	2.55	2.65	2.53	2.68	2.50	2.71
2.5	2.45	2.55	2.43	2.57	2.41	2.60
2.4	2.36	2.45	2.34	2.47	2.31	2.49
2.3	2.26	2.34	2.24	2.36	2.22	2.39
2.2	2.16	2.24	2.15	2.25	2.13	2.28
2.1	2.07	2.13	2.05	2.15	2.04	2.17
2.0	1.97	2.03	1.96	2.04	1.94	2.06
1.9	1.87	1.93	1.86	1.94	1.85	1.96
1.8	1.78	1.83	1.77	1.84	1.75	1.85
1.7	1.68	1.72	1.67	1.73	1.66	1.74
1.6	1.58	1.62	1.57	1.63	1.56	1.64
1.5	1.48	1.52	1.48	1.52	1.47	1.53

ARRI/ZEISS Master Anamorphic 2x MA 180/T2.8 T*XP

Zerstreuungskreisdurchmesser / circle of confusion: 0.030 mm

Gravur Engraving	T-Blende / T-Stop	
	22	
m	von / from	bis / to
hyperfokale Distanz hyperfocal distance	42.40	
INF	42.40	INF
100	29.72	INF
50	22.93	INF
30	17.58	102.17
20	13.61	37.70
15	11.10	23.12
12	9.38	16.67
10	8.11	13.03
8.0	6.75	9.82
7.0	6.03	8.35
6.0	5.27	6.96
5.5	4.88	6.29
5.0	4.49	5.64
4.5	4.08	5.01
4.0	3.67	4.40
3.8	3.50	4.16
3.6	3.33	3.92
3.4	3.16	3.68
3.2	2.99	3.45
3.0	2.81	3.22
2.8	2.64	2.99
2.6	2.46	2.76
2.5	2.37	2.65
2.4	2.28	2.53
2.3	2.19	2.42
2.2	2.10	2.31
2.1	2.01	2.20
2.0	1.92	2.09
1.9	1.83	1.98
1.8	1.73	1.87
1.7	1.64	1.76
1.6	1.55	1.66
1.5	1.46	1.55